

Sport Comfort



Application

This high performance directional tread pattern follows global trends for drive comfort and a quiet ride.

The four circumferential grooves offer excellent straight-line water evacuation, while the solid centre ribs provide good directional stability and steering response.

The Sport Comfort 400 offers superb response, stability and safety at high speeds.

TYRE SIZE	LOAD INDEX	SPEED INDEX	MEASURING RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	MAXIMUM LOAD	MAXIMUM PRESSURE (kPa)	PATTERN DEPTH (mm)
195/50 R15	82	V	6	573	196	475	250	7.9
185/60 R14	82	H	5.5	573	184	475	250	7.9
195/60 R14	86	H	6	585	196	530	250	7.9
195/60 R15	88	H	6	610	202	560	250	7.9
195/60 R15	88	V	6	610	202	560	250	7.9
205/60 R15	91	H	6	628	205	615	250	7.9
205/60 R15	91	V	6	628	205	615	250	7.9
175/65 R14	82	H	5	579	173	475	250	7.9
185/65 R14	86	H	5.5	591	184	530	250	7.9
195/65 R15	91	H	6	629	196	615	250	7.9
195/65 R15	91	V	6	629	196	615	250	7.9
205/65 R15	94	H	6	647	210	670	250	7.9
205/65 R15	94	V	6	647	210	670	250	7.9

 **REGAL**
TYRES
THE SMART CHOICE

Tel + 27 - 31 - 242 1111 Fax + 27 - 31 - 242 1143
 E-mail export@dunlop.co.za Website www.regaltyres.com