

SP SPORT MAXX



APPLICATION

This is a new-generation directional tyre with exceptional driving capability for ultra-high performance vehicles OE homologated on vehicles such as Alfa Romeo, Audi A4 and Audi A6.

Feature: Rigid blocks and optimal contact pressure distribution

Benefit: Provides exceptional dry grip and high speed stability

Feature: Silica compound, wide straight groove

Benefit: Provides superior drainage, excellent wet grip and aquaplaning performance

Feature: Angled 5-pitch chaos pattern arrangement

Benefit: Ensures outstanding quietness.

Tyre Size	Load Index	Speed Index	Run on Flat	Overall Diameter (mm)	Section Width (mm)	Maximum Load (kg)	Maximum Pressure (kPa)	Recommended Rim (J)
215/45 R 17	87	V		626	213	545	250	7.0
225/45 R 17	94	Y		634	225	670	290	7.5
235/45 R 17	94	Y		644	236	670	250	8.0
245/45 R 17	99	Y		652	243	775	250	8.0
215/40 R 17	83	W		604	218	487	250	7.5
245/40 R 17	91	Y		628	248	615	250	8.5
235/50 R 18	97	W		693	245	730	250	7.5
245/45 R 18	100	Y		677	243	800	290	8.0
225/40 R 18	88	Y		637	230	560	250	8.0
235/40 R 18	95	Y		645	241	690	290	8.5
255/40 R 18	99	Y		661	260	775	290	9.0
265/35 R 18	97	Y		643	271	730	290	9.5
275/35 R 18	95	Z		649	278	690	250	9.5

Tel: + 27 (0) 31 242 1111 Fax: + 27 (0) 31 242 1366

E-mail: marketing@dunlop.co.za

Website: www.dunloptyres.co.za



SP SPORT MAXX

Tyre Size	Load Index	Speed Index	Run on Flat	Overall Diameter (mm)	Section Width (mm)	Maximum Load (kg)	Maximum Pressure (kPa)	Recommended Rim (J)
275/55 R 19	111	V		785	284	1 090	250	8.5
235/35 R 19	87	W		647	241	710	250	8.5
245/35 R 19	93	Y		655	248	650	290	8.5
255/30 R 19	91	W		637	260	615	290	9.0
275/30 R 19	96	Y		649	289	710	290	9.5
235/45 R 20	100	W		720	236	800	250	8.0
265/45 R 20	104	Y		746	266	900	250	9.0
275/40 R 20	106	W	ROF	728	289	950	250	9.5
245/35 R 20	91	W		680	248	615	250	8.5
255/35 R 20	97	Y		686	270	650	250	9.0
315/35 R 20	110	W	ROF	728	320	950	250	11.0
245/30 R 20	95	Y		656	248	690	250	8.5
285/25 R 20	93	Y		650	295	650	250	10.5
285/30 R 20	99	Y		680	290	775	290	10.0
285/35 R 21	105	W	ROF	733	302	825	250	10.0
295/35 R 21	107	Y		739	313	975	250	10.5
325/30 R 21	108	W	ROF	729	331	900	250	11.5

Tel: + 27 (0) 31 242 1111 Fax: + 27 (0) 31 242 1366

E-mail: marketing@dunlop.co.za

Website: www.dunloptyres.co.za

