

# SP SPORT 9000



## APPLICATION

An ultra-high performance tyre with an advanced unidirectional tread pattern that fans outwards and utilises a silica compound for the tread. This tyre uses innovative construction and a new rubber polymer technology to ensure reduced aquaplaning, better wet and dry handling, improved stability, shorter braking distances and reduced fuel consumption. Ideal for high performance cars providing high safety reserves even in unexpected situations.

**Feature:** Directional, silica compound tread pattern

**Benefit:** Massive grip and precise handling control, wet or dry

**Feature:** Jointless Band (JLB) aramid casing construction

**Benefit:** Lower unsprung weight. Superb uniformity for smoothness

**Feature:** Maximum flange shield rim protection (MFS)

**Benefit:** Reduces accidental wheel damage

**Feature:** Base pen electrostatic discharge system

**Benefit:** Prevents static electricity build up. No shocks, no sparks, safer fuelling.

Tyre Size	Load Index	Speed Index	Run on Flat	Overall Diameter (mm)	Section Width (mm)	Maximum Load (kg)	Maximum Pressure (kPa)	Recommended Rim (J)
215/55 R 16	93	Y		642	226	650	250	7.0
225/55 R 16	95	W		654	233	690	250	7.0
225/50 R 16	92	Z		632	233	630	250	7.0
235/55 R 17	99	Y		690	245	775	250	7.5
205/45 R 17	84	V	DSST	616	206	500	250	7.0
245/45 R 17	95	W		652	243	690	250	8.0
255/45 R 17	98	W		662	255	750	250	8.5
255/40 R 17	94	Y		636	260	670	250	9.0

Tel: + 27 (0) 31 242 1111 Fax: + 27 (0) 31 242 1366

E-mail: [marketing@dunlop.co.za](mailto:marketing@dunlop.co.za)

Website: [www.dunloptyres.co.za](http://www.dunloptyres.co.za)



# SP SPORT 9000

Tyre Size	Load Index	Speed Index	Run on Flat	Overall Diameter (mm)	Section Width (mm)	Maximum Load (kg)	Maximum Pressure (kPa)	Recommended Rim (J)
255/55 R 18	105	W		737	265	925	250	8.0
235/50 R 18	101	Y		693	245	730	250	7.5
285/50 R 18	109	W		743	297	1 030	250	9.0
255/45 R 18	99	Y		688	260	775	250	8.5
225/40 R 18	88	W		637	230	560	250	8.0
245/40 R 18	93	Z		653	253	650	250	8.5
275/40 R 18	99	Y		677	278	775	250	9.5
255/35 R 18	94	Z		635	260	670	250	9.0
265/35 R 18	93	Z		645	270	650	250	9.5
295/45 R 19	100	Z		749	296	1 030	250	10.0
255/40 R 19	100	Y		687	260	710	250	9.0

Tel: + 27 (0) 31 242 1111 Fax: + 27 (0) 31 242 1366

E-mail: [marketing@dunlop.co.za](mailto:marketing@dunlop.co.za)

Website: [www.dunloptyres.co.za](http://www.dunloptyres.co.za)

