






APPLICATION

This all wheel position tyre for ordinary highway usage is well suited to mid and short distance vehicles, designed to give longer life with a reinforced bead structure that improves durability. Benefits include:

- Longer life due to deep main groove
- A compound designed to give a more wear resistant tread
- Zigzag circumferential grooves and transverse grooves on the shoulder that ensure a firm and steady ride.



Recommended

-	OK	

Tyre Size	Ply Rating	Load Index	Speed Index	TL or TT	Overall Diameter (mm)	Section Width (mm)	Maximum load per tyre. Single (kg)	Maximum load per tyre. Dual (kg)	Maximum Pressure (kPa)	Recommended Rim (J)	Tread Depth (mm)
12.00R20	18	154/150	К	TT	1125	308	3750	3350	850	8.50	15.6
12R22.5	18	152/148	L	TL	1076	312	3550	3150	850	9.00	16.3
315/80R22.5	18	154/150 156/150	M L	TL	1076	312	3750 4000	3350	830	9.00	16.1

*DECTES (Dunlop Energy Control Technologies) is a combination of innovative design technologies aimed at controlling heat energy build-up and energy loss whilst ensuring a more consistent contact patch; resulting in lower rolling resistance, higher mileage, a more wear resistant tread and a reduction in uneven tread wear all contributing to excellent CPK.

E-mail: marketing@srigroup.co.za **Website:** www.dunloptyres.co.za



