


SP 882/SP 882A*

Drive Position, Long Haul Highway

DECTES*

APPLICATION

This highway usage tyre is a robust, high-mileage tubeless radial tyre offering superior traction and long haul performance as well as excellent CPK.



Recommended

Tyre Size	Ply Rating	Load Index	Speed Index	TL or TT	Overall Diameter (mm)	Section Width (mm)	Maximum load per tyre. Single (kg)	Maximum load per tyre. Dual (kg)	Maximum Pressure (kPa)	Recommended Rim (J)	Tread Depth (mm)
12R22.5	18	152/149	L	TL	1085	300	3550	3250	850	9.00	23.9
295/80R22.5	18	152/148	Μ	TL	1059	306	3550	3150	850	9.00	18.7
*315/80R22.5	18	154/150 156/150	M L	TL	1076	312	3750 4000	3350	830 850	9.00	21.1

*DECTES (Dunlop Energy Control Technologies) is a combination of innovative design technologies aimed at controlling heat energy build-up and energy loss whilst ensuring a more consistent contact patch; resulting in lower rolling resistance, higher mileage, a more wear resistant tread and a reduction in uneven tread wear all contributing to excellent CPK.

E-mail: marketing@srigroup.co.za **Website:** www.dunloptyres.co.za



